STEPS

HRCL - Wall Mount



PROJECT DATE

COMMENTS

STANDARD FEATURES

- Die-Cast Louvered Aluminum Faceplate
- Prismatic Tempered Glass Lens
- Galvanized Steel And Powder Coated Back Box
- Suitable For Concrete Or Non Insulated Wall
- Closed Cell Continuous Neoprene Gasket













SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	OPTIONS
HRCL	5000	S = Small	LED	800	K27 = 2700K	120-277 UNV	DD = 0-10V Dimming Driver	TAL = Textured Aluminum	NLU = No Louver Face Plate*
		M = Medium			K3 = 3000K			TBK = Textured Black	OPL = Opal Polycarbonate Lens
					K35 = 3500K			TBZ = Textured Bronze	
					K4 = 4000K			TWH = Textured White	
					K5 = 5000K			CC = Custom Color	
								RAL = RAL Color	
ORDERING INFORMATION									
SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	OPTIONS

ORDERING EXAMPLE: HRCL - 5000 - M - LED - 800 - K3 - 120/277 - TBZ - OPL *Small size only

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

Programmable drivers at the PACE factory Color tunable

Capable of remote dimming

4. Can be equipped with motion sensors for on/off functioning

Can be equipped with light sensors for dusk-to-dawn automatic on/off operation Bluetooth commissioning sensor capability for Android and iOS 5. 6.



STEPS

HRCL - Wall Mount



SIZES

Small = 10.5" x 4.3"

Medium = 10.5" x 5.3"

MOUNTING


· Recessed Wall


COLOR

- Textured or smooth polyester powder coat finishes
- · RAL colors optional

DIMENSIONS

Small







Medium

