ROBUSTO

AESW - Shaped Wedge



PROJECT DATE

COMMENTS

STANDARD FEATURES

- Architectural Shape Wedge
- Heavy Gauge Formed Aluminum Construction
- High Performance Optical System















SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	OPTICS	MOUNTING	OPTIONS
AESW	1620	S = SMALL L = LARGE	LED	1500 to 6000	K27 = 2700K K3 = 3000K K35 = 3500K K4 = 4000K K5 = 5000K	120/277 UNV	DD = 0-10V Dimming Driver	TAL = Textured Aluminum TBK = Textured Black TBZ = Textured Bronze TWH = Textured White CC = Custom Color RAL = RAL Color	II = TYPE II III = TYPE III V = TYPE V	WMDL = Wall Mount Downlight WMUL = Wall Mount Uplight YM = Yoke Mount 2YM = 2 Yoke Mount BM/S = Bollard Mount Single BM/D = Bollard Mount Double PM = Pole Mount	EM = Emergency Backup MS = Motion Sensor PE1 = Photocell 120V PE2 = Photocell 277V
ORDERING INFORMATION											
SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	OPTICS	MOUNTING	OPTIONS

ORDERING EXAMPLE: AESW - 1620 - L - LED - 4500 - K4 - 120/277 - DD - TWH - III - WMUL - PE1

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

- Programmable drivers at the PACE factory Color tunable
- Capable of remote dimming

- Can be equipped with motion sensors for on/off functioning
- Can be equipped with light sensors for dusk-to-dawn automatic on/off operation Bluetooth commissioning sensor capability for Android and iOS



ROBUSTO

Small = 12" x 21"

Large = 20" x 36"

AESW - Shaped Wedge



SIZES

MOUNTING

- · Wall Mount, bollard, yoke mount
- · See technical data sheets for other mounting


COLOR

Textured polyester powder coat finishes

DIMENSIONS


WMDL

Wall Mount Downlight




WMUL

Wall Mount Uplight




РМ

Pole Mount




BM/S

Bollard Mount Single




Yoke Mount




2YM

2 Yoke Mount



		_		_	
42"					
_	<u>•</u>		 19"		<u> </u>





	W	Н	D	Α	В	С	EPA
Small	12"	12"	8"	1.0"	21.0"	18.3"	1.8
Large	20.0"	20.0"	14.2"	1.5"	36.0"	32.0"	2.3