RONDELLA

ROND 3 - Luminous Dome Top



PROJECT DATE

COMMENTS

STANDARD FEATURES

- Two Piece Heavy Gauge Spun Aluminum Domed Housing
- High Performance Optical System















SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	BEAM ANGLE	MOUNTING	OPTIONS
ROND3	1690	L = 20" Diameter	LED	10000 to 65000	K27 = 2700K K3 = 3000K K35 = 3500K K4 = 4000K K5 = 5000K	120-277V UNV	DD = 0-10V DIMMING DRIVER	TAL = Textured Aluminum TBK = Textured Black TBZ = Textured Bronze TWH = Textured White CC = Custom Color RAL = RAL Color	60 = 60° Angle 90 = 90° Angle 120 = 120° Angle	WM = Wall Mount PAM = Pole Arm Mount PAM2/180 = 2 Arms at 180° PAM2/190 = 2 Arms at 90° PAM3/120 = 3 Arms at 120° PAM4/90 = 4 Arms at 90°	MS = Motion Sensor PE1 = Photocell 120V PE2 = Photocell 277V
						ORDERIN	IG INFORMA	ATION			
SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	BEAM ANGLE	MOUNTING	OPTIONS

ORDERING EXAMPLE: ROND3 - 1690 - L - LED - 22500 - K4 - 120/277 - DD - TWH - 90 - PAM - PE1

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

- Programmable drivers at the PACE factory Color tunable
- Capable of remote dimming

- Can be equipped with motion sensors for on/off functioning Can be equipped with light sensors for dusk-to-dawn automatic on/off operation Bluetooth commissioning sensor capability for Android and iOS



RONDELLA

ROND 3 - Luminous Dome Top



SIZES

- Small = 17" diameter
- · Medium = 22" diameter

MOUNTING


- Yoke mount, Wall mount, Pole arm mount
- See technical data sheets for details

COLOR


- Textured or smooth polyester powder coat finishes
- · RAL colors available

DIMENSIONS

Small / EPA = 0.8



Medium / EPA = 1.1



Yoke Mount

