CILINDRO

EUDC-V - Cylinder



PROJECT DATE

COMMENTS

STANDARD FEATURES

- Powered suspension systems both power and suspend your Class 2 LED lighting fixtures with a thin cable, providing a clean, modern and elegant look without the need for a separate power cord.
- Heavy Gauge Housing
- Stainless Steel Hardware
- Silicone Gasket
- Acrylic Lens
- Factory Programmable Driver
- No Bulky Power Cords Needed
- · Clean, Modern Look
- Easy Field Installation
- Labor-Saving Tool-Free Installation
- Quickly Adjust And Re-Adjust To Any Height
- 19" Standard Length















SERIES	MODEL	SIZE	LAMP	LUMENS	ССТ	VOLT	CONTROL	COLOR	OPTIONS
EUDC-V	900	6 = 6" Diameter	LED	1500 to 4000	K27 = 2700K K3 = 3000K K35 = 3500K K4 = 4000K K5 = 5000K	120/277 UNV	DD = 0-10V Dimming Driver	TAL = Textured Aluminum TBK = Textured Black TBZ = Textured Bronze TWH = Textured White CC = Custom Color RAL = RAL Color	MS = Motion Sensor EM = Emergency Backup DL = Downlight Only UP/DW = Up and Downlight CLXX = Custom Length Body
ORDERING INFORMATION									
SERIES	MODEL	SIZE	LAMP	LUMENS	ССТ	VOLT	CONTROL	COLOR	OPTIONS

ORDERING EXAMPLE: EUDC-V - 900 - 6 - LED - 2000 - K4 - 120/277 - DD - TBK - UP/DW

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

- Programmable drivers at the PACE factory
- Color tunable Capable of remote dimming

- Can be equipped with motion sensors for on/off functioning
- Can be equipped with light sensors for dusk-to-dawn automatic on/off operation Bluetooth commissioning sensor capability for Android and iOS





Although PACE has prepared the information contained in this document with all due care, PACE does not warrant or represent that the information is free from errors or omission

CILINDRO

EUDC-V - Cylinder



SIZES

· 6" diameter

COLOR

- Textured or smooth polyester powder coat finishes
- · RAL colors available

DIMENSIONS



