# **STEPS** HRCL - Wall Mount

PROJECT

DATE



COMMENTS

## STANDARD FEATURES

- Die-Cast Louvered Aluminum Faceplate
- Prismatic Tempered Glass Lens •
- Galvanized Steel And Powder Coated Back Box
- Suitable For Concrete Or Non Insulated Wall .
- Closed Cell Continuous Neoprene Gasket ٠





SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	OPTIONS
HRCL	5000	S = Small	LED	800	<b>K27</b> = 2700K	120-277 UNV	DD = 0-10V Dimming Driver	TAL = Textured Aluminum	NLU = No Louver Face Plate*
		<b>M</b> = Medium			<b>K3</b> = 3000K			<b>TBK</b> = Textured Black	<b>OPL</b> = Opal Polycarbonate Lens
					<b>K35</b> = 3500K			<b>TBZ</b> = Textured Bronze	
					<b>K4</b> = 4000K			TWH = Textured White	
					<b>K5</b> = 5000K			CC = Custom Color	
								RAL = RAL Color	
ORDERING INFORMATION									
SERIES	MODEL	SIZE	LAMP	LUMENS	CCT CRI 80	VOLT	CONTROL	COLOR	OPTIONS

ORDERING EXAMPLE: HRCL - 5000 - M - LED - 800 - K3 - 120/277 - TBZ - OPL

\*Small size only

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

Programmable drivers at the PACE factory 1 Color tunable

2 3.

Capable of remote dimming

- 4. Can be equipped with motion sensors for on/off functioning
- Can be equipped with light sensors for dusk-to-dawn automatic on/off operation Bluetooth commissioning sensor capability for Android and iOS 5. 6.

PACE Illumination 5500 West 111th Street | Oak Lawn, Illinois 60453 | 708-499-1700 | quotes@paceillumination.com Although PACE has prepared the information contained in this document with all due care, PACE does not warrant or represent that the information is free from errors or omission. Whilst the information is considered to be true and correct at the date of publication, changes in circumstances after the time of publication may impact on the accuracy of the information. The information may change without notice and PACE is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

In the interest of product improvement, Pace reserves the right to make technical and product specification changes without notice. Consult factory for voltage and other lamp options.

# **STEPS** HRCL - Wall Mount




#### SIZES


# MOUNTING


- Small = 10.5" x 4.3"
- Medium = 10.5" x 5.3"
- Recessed Wall
- COLOR
- Textured or smooth polyester powder coat finishes
- RAL colors optional

## DIMENSIONS










¢

No Louver Face Plate





PACE Illumination 5500 West 111th Street | Oak Lawn, Illinois 60453 | 708-499-1700 | quotes@paceillumination.com

Although PACE has prepared the information contained in this document with all due care, PACE does not warrant or represent that the information is free from errors or omission. Whilst the information is considered to be true and correct at the date of publication, changes in circumstances after the time of publication may impact on the accuracy of the information. The information may change without notice and PACE is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.